



BEARING COMPANY 1401 PIEDMONT TROY, MI 48083
 PH: (248)528-2020 FAX: (248) 528-0920



RULON & COMPOSITE WAY STRIP MATERIAL

Rulon® LR

Rulon® J

Rulon® 142


Rulon® 641

Laminate Composite

Thickness

.015
(+,- .001)

.015



.020
.025
.031
(+,- .002)

.020
.031
(+,- .002)

.020
.031
(+,- .002)

.031
(+,- .002)

.045
.062
(+,- .003)

.062
(+,- .003)

.045
.062
(+,- .003)

.062
(+,- .015)

.090
.125
(+,- .005)

.090
.125
(+,- .005)

.125
(+,- .005)

.125
.187
.250
(+,- .015)

Rulon® is etched on one side for normal service with 2 step epoxy system.

Standard width 12", thinner widths available for an additional cutting charge.

Rulon® is available in continuous rolls or cut to length.
 Non standard sizes of Rulon® available to .250 " thick.

Laminate composite is polyseter material impregnated with thermal setting resins.
 Material is available in standard sheets 24" x 48" (larger sheets by request), max. 2".

Bonding of all Rulon® and laminate composite material to steel, aluminum and other sunstrates, processed at our Troy plant. Other PTFE composites including Rulon® F, Glass filled, Virgin PTFE Metaloplast are available for bonding. Discuss high temp bonding applications with Tech Services.